Industrial

### Product Handling Information Sheet Maywotron<sup>®</sup> ABS/TPU Sur-R

1. Company			
Name/Address	Röchling Industrial Allgäu GmbH Hinter den Gärten 20 • 87730 Bad Grönenbach/Germany (DE) • Tel. +49 8334 9857 0 info@roechling-maywo.de • www.roechling.com/industrial/groenenbach		
2. Product details			
Product/Article	Technical semi-finished product or machined part		
Abbreviated terms	ABS / TPU		
Material Characterisation	Thermoplastic		
Main Components	<ul> <li>acrylonitrile butadiene styrene</li> <li>thermoplastic polyurethanes</li> <li>colour pigments and possibly additives</li> </ul>		
Components Subject to labelling	none		
Classification according to REACh	Article		
Notes	-		
3. Product characteristics			
Form/State	• firm		
Color	-		
Odour	nearly odourless		
Density	1,10		
Melting range	>180°C		
Glass transition temperature	-		
Thermal decomposition	>230°C		



# Röchling

3. Product characteristics			
Flash point	-		
gnition temperature	> 350°C		
Notes	-		

Special Risks For Mankind And T Environment	ne none
Notes	-
5. Handling and Storage	
Handling	<ul> <li>Product can be worked with conventional machines and tools.</li> <li>Before machining the product should have room temperature and/or to be stored for min. 24h under normal climatic conditions.</li> </ul>
Storage	<ul> <li>horizontally</li> <li>dry</li> <li>protected against frost</li> <li>protected against climatic influences</li> <li>product protect against frost</li> </ul>
Safety measures	<ul> <li>Provide suitable exhaust ventilation at the drying process and in the area surrounding the melt outlet of processing machines.</li> <li>Wear gloves to prevent contact during mechanical processing and/or hot mel conditions.</li> <li>Wear splash goggles to protect from hot molten substance/product.</li> </ul>
Shelf Life	-
Notes	-

6. Transport	
Transport	<ul> <li>Non dangerous goods according to the transport regulations</li> <li>Secure against slipping.</li> </ul>
Finished Product Packing	-
Notes	_



## Röchling

7. Fire – fighting measure			
Suitable extinguishing age	<ul> <li>water</li> <li>foam</li> <li>CO<sub>2</sub></li> <li>dry powder extinguishing agents</li> </ul>	<ul> <li>foam</li> <li>CO<sub>2</sub></li> </ul>	
Potential combustion pro	<ul> <li>CO</li> <li>CO<sub>2</sub></li> <li>HCN</li> <li>NO</li> <li>isocyanate</li> </ul>		
Necessary protection equ	• Complete protection equipment for fire-brigade.		
Notes	Molten product has to be cooled with water. Fire residues and core extinguishing water must be collected and disposed of according instructions.		
8. Removal			
Recyclability	Check possibility of recycling.		
EC Waste Catalog	The product is classified in accordance with the European-Waste (EWC) as "not dangerous".	Catalogue	
Waste Removal	Has to be conveyed to a suitable dumping site or combustion pla with local regulations.	nt in accordance	
EC Waste Code	<ul><li>12 01 05 plastics shavings and turnings</li><li>20 01 39 plastics</li></ul>		
Notes			
0 Marilia and Cuidelia a			
9. Marking and Guidelines	550 and labelling as a wind		
Marking in accordance wi Guideline	EEC no labelling required		
Notes	-		



Print: 28/04/2024 • Release: 20/09/2023 • Version: 1.0 PIM-Version: 85 • PIM-ID: 709702 • PIM-Code: 85-8



#### Industrial

Information about REACh According to EC directive 1907/2006/EC (REACh), Article 3, no.3 our products are clearly defined as articles, exempt from registration. The EU regulation about chemicals no. 1907/2006 (REACh), which came into force 01 st of June 2007, prescribes Material Safety Data Sheets only for dangerous substances and preparations. According to REACh we are manufacturing articles and, therefore, not required to issue safety sheets.

#### 11. Other Information

Other Information

The information in this document are based on our today's knowledge and represent no affirmation of characteristics.Existing laws and regulations are to be observed by the user of our product within his own responsibility.



Print: 28/04/2024 • Release: 20/09/2023 • Version: 1.0 PIM-Version: 85 • PIM-ID: 709702 • PIM-Code: 85-8