

Technical Data Sheet

Polystone[®] Extreme Wear dump bed liner

PE-UHMW / PE 1000

Typical characteristics

- Good sliding properties
- High impact resistance
- High abrasion resistance

Typical industries

- Heavy-Duty Truck Products

	Test method	Unit	Guideline value
General properties			
Density	ASTM D792	g / cm ³	0.93
Mechanical properties			
Tensile Strength at Yield	ASTM D638	psi	2800
Elongation at Break	ASTM D638	%	400
Flexural Modulus	ASTM D790	psi	90000
Rockwell Hardness	ASTM D785	R	67
Thermal properties			
Continuous Use		°F	180
Electrical properties			
Volume Resistivity	ASTM D257	Ωcm	>10 ¹⁶
Surface resistivity	ASTM D257	Ω/cm	>10 ¹⁶

The data stated above are average values ascertained by statistical tests on a regular basis. The data above are provided purely for information and shall not be regarded as binding unless expressly agreed in a contract of sale.

ri-inquiry@roechling.com • www.roechling.com/industrial/materials

Print: 20/04/2026 • Release: 20/08/2025 • Version: 2.0

PIM-ID: 717988 • PIM-Code: 45-21-223.18.63-6-2

Company-IDs: 23070

Page 1 / 1 (Dates in DD/MM/YYYY)

