

Product Handling Information Sheet

Foamlite® P 652 + UV-stabilized PIR bicolor

1. Company

Name/Address **Röchling Industrial SE & Co. KG**
Röchlingstr. 1 • 49733 Haren (Ems)/Germany (DE) • Tel. +49 5934 701-0
info@roechling-plastics.com • www.roechling.com/industrial/haren

2. Product details

Product/Article	Technical semi-finished product or machined part
Abbreviated terms	PP
Material Characterisation	Semi crystalline plastic
Main Components	<ul style="list-style-type: none"> • polypropylene • stabiliser • additives
Components Subject to labelling	none
Classification according to REACH	Article
Notes	This product is a post-industrial recycled article. See Chapter 11.

3. Product characteristics

Form/State	<ul style="list-style-type: none"> • firm
Color	bicolor
Odour	<ul style="list-style-type: none"> • nearly odourless
Density	0,65
Melting range	162 ... 167
Glass transition temperature	-
Thermal decomposition	> 390°C
Flash point	≈ 340°C

3. Product characteristics

Ignition temperature	> 300°C
Notes	–

4. Danger warnings

Special Risks For Mankind And The Environment	none
Notes	–

5. Handling and Storage

Handling	<ul style="list-style-type: none"> • Product can be worked with conventional machines and tools. • Before machining the product should have room temperature and/or to be stored for min. 24h under normal climatic conditions.
Storage	<ul style="list-style-type: none"> • horizontally • dry • protected against climatic influences
Safety measures	
Shelf Life	–
Notes	–

6. Transport

Transport	<ul style="list-style-type: none"> • Non dangerous goods according to the transport regulations. • Secure against slipping.
Finished Product Packing	–
Notes	–

7. Fire – fighting measures

Suitable extinguishing agents	<ul style="list-style-type: none"> • water • foam • CO₂ • dry powder extinguishing agents
Potential combustion products	<ul style="list-style-type: none"> • CO • CO₂
Necessary protection equipment	<ul style="list-style-type: none"> • Complete protection equipment for fire-brigade.
Notes	Molten product has to be cooled with water. Fireresidues must be collected and disposed according to the local instructions.

8. Removal

Recyclability	Check possibility of recycling.
EC Waste Catalog	The product is classified in accordance with the European-Waste Catalogue (EWC) as "not dangerous".
Waste Removal	Has to be conveyed to a suitable dumping site or combustion plant in accordance with local regulations.
EC Waste Code	<ul style="list-style-type: none"> • 12 01 05 plastics shavings and turnings • 20 01 39 plastics
Notes	-

9. Marking and Guidelines

Marking in accordance with EEC Guideline	no labelling required
Notes	-

10. Information about REACH

Information about REACH	According to EC directive 1907/2006/EC (REACH), Article 3, no.3 our products are clearly defined as articles, exempt from registration. The EU regulation about chemicals no. 1907/2006 (REACH), which came into force 01 st of June 2007, prescribes Material Safety Data Sheets only for dangerous substances and preparations. According to REACH we are manufacturing articles and, therefore, not required to issue safety sheets.[]
-------------------------	---

11. Other Information



Other Information

The information in this document are based on our today's knowledge and represent no affirmation of characteristics. Existing laws and regulations are to be observed by the user of our product within his own responsibility. --- Post-industrial recycled material is material that is generated during the manufacturing as waste for recycling process (see waste) and can only be reused through recycling. This does not mean a material that can be used again directly in the same process without recycling.

