

Product Handling Information Sheet

≈ 340°C

Foamlite® P 652 + UV-stabilized white

1. Company	
Name/Address	Röchling Industrial SE & Co. KG Röchlingstr. 1 • 49733 Haren (Ems)/Germany (DE) • Tel. +49 5934 701-0 info@roechling-plastics.com • www.roechling.com/industrial/haren
2. Product details	
Product/Article	Technical semi-finished product or machined part
Abbreviated terms	PP
Material Characterisation	Semi crystalline plastic
Main Components	polypropylenestabiliseradditives
Components Subject to labellin	ng none
Classification according to REA	ACh Article
Notes	
3. Product characteristics	
Form/State	• firm
Color	white
Odour	nearly odourless
Density	0,65
Melting range	162 167
Glass transition temperature	-
Thermal decomposition	> 390°C



Flash point



roduct can be worked with conventional machines and tools. efore machining the product should have room temperature and/or to be cored for min. 24h under normal climatic conditions. prizontally ry rotected against climatic influences					
roduct can be worked with conventional machines and tools. efore machining the product should have room temperature and/or to be cored for min. 24h under normal climatic conditions. orizontally					
roduct can be worked with conventional machines and tools. efore machining the product should have room temperature and/or to be cored for min. 24h under normal climatic conditions. orizontally					
roduct can be worked with conventional machines and tools. efore machining the product should have room temperature and/or to be cored for min. 24h under normal climatic conditions. orizontally					
efore machining the product should have room temperature and/or to be cored for min. 24h under normal climatic conditions. prizontally					
efore machining the product should have room temperature and/or to be cored for min. 24h under normal climatic conditions. prizontally					
efore machining the product should have room temperature and/or to be cored for min. 24h under normal climatic conditions. prizontally					
efore machining the product should have room temperature and/or to be cored for min. 24h under normal climatic conditions. prizontally					
efore machining the product should have room temperature and/or to be cored for min. 24h under normal climatic conditions. prizontally					
Y					
 Non dangerous goods according to the transport regulations. Secure against slipping. 					



Industrial



• water		
• foam		
• CO ₂		
dry powder extinguishing agents		
• CO		
• CO ₂		
Complete protection equipment for fire-brigade.		
Molten product has to be cooled with water. Fireresidues must be collected and disposed according to the local instructions.		

8. Removal	
Recyclability	Check possibility of recycling.
EC Waste Catalog	The product is classified in accordance with the European-Waste Catalogue (EWC) as "not dangerous".
Waste Removal	Has to be conveyed to a suitable dumping site or combustion plant in accordance with local regulations.
EC Waste Code	12 01 05 plastics shavings and turnings20 01 39 plastics
Notes	-

9. Marking and Guidelines					
Marking in accordance with Guideline	EEC	no labelling r	required		
Notes		-			

10. Information about REACh	
Information about REACh	According to EC directive 1907/2006/EC (REACh), Article 3, no.3 our products are clearly defined as articles, exempt from registration. The EU regulation about chemicals no. 1907/2006 (REACh), which came into force 01 st of June 2007, prescribes Material Safety Data Sheets only for dangerous substances and preparations. According to REACh we are manufacturing articles and, therefore, not required to issue safety sheets.

11. Other Information







Other Information

The information in this document are based on our today's knowledge and represent no affirmation of characteristics. Existing laws and regulations are to be observed by the user of our product within his own responsibility.



