

Product Handling Information Sheet

Lignostone[®] M I-2-E3-SQ

1. Company	
Name/Address	Röchling Industrial SE & Co. KG Röchlingstr. 1 • 49733 Haren (Ems)/Germany (DE) • Tel. +49 5934 701-0 info@roechling-plastics.com • www.roechling.com/industrial/haren
2. Product details	
Product/Article	Technical semi-finished product or machined part
Abbreviated terms	Laminated Densified Wood
Material Characterisation	Wooden veneer with phenolic resin in hardened condition
Main Components	wooden veneerphenolic resin
Components Subject to labelling	none
Classification according to REACh	Article
Notes	-
3. Product characteristics	
Form/State	• firm
Color	-
Odour	typical material smell
Density	-
Melting range	-
Glass transition temperature	-
Thermal decomposition	-
Flash point	None, with intended use





3. Product characteristics	
Ignition temperature	-
Notes	
4. Danger warnings	
Special Risks For Mankind A Environment	d The Note the TRGS 553 wooden dust.
Notes	Category III A1: However, with the footnote "dust epidemiologically" unequivocally carcinogenic: The causative, cancer-producing principle currently not yet identified. After sensitisation, wood dust may cause allergic phenomena for example, of the skin or respiratory passages. Publication (Holzzentralblatt KW29/00): A carcinogenic effect refers to chemically treated wood with additiv of chromates, lindane and PCP. These substances are not used in the production of Lignostone.
5. Handling and Storage	
Handling	Product can be worked with conventional machines and tools.
Storage	 horizontally dry protected against frost protected against climatic influences humidity level in the shop floor and warehouse should be maintained below 65% to improve shelf life of materials
Safety measures	 Provide effective dust extraction when processing and machining. Carry protective mask and protective goggles at dusty condition. Should dust extraction systems not be available
Shelf Life	Lignostone materials have a long shelf life if not directly in contact with water and liquids. The materials, if stocked properly, have a long shelf life, however, for the sake of control, 36 months to 48 months could be set as the limit. Moisture absorption from the atmosphere happens from the edges of the material. The absorbed moisture is normally within the specifications of IEC 61061. Moisture evacuates easily during vapor phase. During visual inspection, if only the edges a sheet are swollen above 10% in thickness, the sheet should not be used in full format. Not to be confused with: For thick sheets above 70mm, and all sheets large format sheets above 2m in width, thickness tolerance of the sheet is high and may be as high as 15%. This within specified tolerance expansion is a natura property of the material and not due to moisture absorption.





5. Handling and Storage	
Notes	The product is more or less hygroscopic depending on the compaction level. Work stations and machines must be regularly cleaned of dust deposits and shavings by being absorbed. Blowing them clear with compressed air is not admissible on principle.
6. Transport	
Transport	Non dangerous goods according to the transport regulations.Secure against slipping.
Finished Product Packing	Machined parts are tailor made as per customers' designs. It is normal to receive packing instructions from the customers and these shall be followed In the case of semi-finished sheets, it is advisable to always transfer materials in a palletized form, and protective covering that prevents water and dust entry into the materials.
Notes	-
7. Fire – fighting measures	
Suitable extinguishing agents	waterfoamCO₂
Potential combustion products	• CO • CO ₂ • other toxic gases
Necessary protection equipment	Complete protection equipment for fire-brigade.
Notes	Do not whirl up smouldering fires in dust deposits with a full water jet – dust explosion hazard.
8. Removal	
Recyclability	Check possibility of recycling.
EC Waste Catalog	The product is classified in accordance with the European-Waste Catalogue (EWC) as "not dangerous".
Waste Removal	Has to be conveyed to a suitable dumping site or combustion plant in accordance with local regulations.
EC Waste Code	







8. Removal		
Notes		. -
9. Marking and Guidelines		
Marking in accordance with EEC Guideline		no labelling required
Notes		-
10. Information about REACh Information about REACh		According to EC directive 1907/2006/EC (REACh), Article 3, no.3 our products are clearly defined as articles, exempt from registration. The EU regulation about chemicals no. 1907/2006 (REACh), which came into force 01 st of June 2007, prescribes Material Safety Data Sheets only for dangerous substances and preparations. According to REACh we are manufacturing articles and, therefore, not required to issue safety sheets.
11. Other Information		
Other Information		The information in this document are based on our today's knowledge and represent no affirmation of characteristics. Existing laws and regulations are to be observed by the user of our product within his own responsibility.

