

## **Product Handling Information Sheet**

## Polystone<sup>®</sup> G black

| 1. Company                        |  |  |  |  |  |
|-----------------------------------|--|--|--|--|--|
| Name/Address                      | Röchling Industrial Lahnstein SE & Co. KG Sustaplast-Str. 1 • 56112 Lahnstein/Germany (DE) • Tel. +49 2621 693-0 info.lahnstein@roechling.com • www.roechling.com/industrial/lahnstein |  |  |  |  |
|                                   |  |  |  |  |  |
| 2. Product details                |  |  |  |  |  |
| Product/Article                   | Technical semi-finished product or machined part   |  |  |  |  |
| Abbreviated terms                 | PE-HD / PE 300   |  |  |  |  |
| Material Characterisation         | Semi crystalline plastic   |  |  |  |  |
| Main Components                   | <ul><li>polyethylene</li><li>stabiliser</li><li>additives</li></ul>  |  |  |  |  |
| Components Subject to labelling   | none   |  |  |  |  |
| Classification according to REACh | -  |  |  |  |  |
| Notes                             |  |  |  |  |  |
| 3. Product characteristics        |  |  |  |  |  |
| Form/State                        | • firm   |  |  |  |  |
| Color                             | black  |  |  |  |  |
| Odour                             | nearly odourless   |  |  |  |  |
| Density                           | 0,95   |  |  |  |  |
| Melting range                     | 131  |  |  |  |  |
| Glass transition temperature      | -  |  |  |  |  |
| Thermal decomposition             | > 390°C  |  |  |  |  |
| Flash point                       | ≈ 340°C  |  |  |  |  |
|                                   |  |  |  |  |  |





| lauditian tanan anatuwa                          | . 7F0°C   |
|--|---|
| Ignition temperature                             | > 350°C   |
| Notes  | <u>-</u>  |
| 4. Danger warnings                               |   |
| Special Risks For Mankind And The<br>Environment | none  |
| Notes  |   |
|  |   |
| 5. Handling and Storage                          |   |
| Handling   | <ul> <li>Product can be worked with conventional machines and tools.</li> <li>Before machining the product should have room temperature and/or to be stored for min. 24h under normal climatic conditions.</li> </ul> |
| Storage  | <ul> <li>horizontally</li> <li>dry</li> <li>protected against frost</li> <li>protected against climatic influences</li> </ul>   |
| Safety measures                                  |   |
| Shelf Life                                       |   |
| Notes  | +   |
|  |   |
| 6. Transport                                     |   |
| Transport  | <ul> <li>Non dangerous goods according to the transport regulations.</li> <li>Secure against slipping.</li> </ul>   |
| Finished Product Packing                         | -   |
| Notes  | _   |
|  |   |



7. Fire – fighting measures





| Suitable extinguishing agents  | • water  |
|--------------------------------|--|
|                                | • foam   |
|                                | • CO <sub>2</sub>  |
|                                | <ul> <li>dry powder extinguishing agents</li> </ul>  |
| Potential combustion products  | • CO   |
|                                | • CO <sub>2</sub>  |
| Necessary protection equipment | Complete protection equipment for fire-brigade.  |
| Notes                          | Molten product has to be cooled with water. Fireresidues must be collected and disposed according to the local instructions. |

| 8. Removal       |   |
|------------------|---|
| Recyclability    | Check possibility of recycling.   |
| EC Waste Catalog | The product is classified in accordance with the European-Waste Catalogue (EWC) as "not dangerous".     |
| Waste Removal    | Has to be conveyed to a suitable dumping site or combustion plant in accordance with local regulations. |
| EC Waste Code    | <ul><li>12 01 05 plastics shavings and turnings</li><li>20 01 39 plastics</li></ul>                     |
| Notes            | -   |

| 9. Marking and Guidelines            |     |                |         |  |  |  |
|--------------------------------------|-----|----------------|---------|--|--|--|
| Marking in accordance with Guideline | EEC | no labelling r | equired |  |  |  |
| Notes                                |     | _              |         |  |  |  |

| 10. Information about REACh |                              |  |
|-----------------------------|------------------------------|--|
| ormation about REACh        | Information about REACh Text |  |

| 11. Other Information |   |
|-----------------------|---|
| Other Information     | The information in this document are based on our today's knowledge and represent no affirmation of characteristics. Existing laws and regulations are to be observed by the user of our product within his own responsibility. |

