Industrial

Product Handling Information Sheet Polystone[®] M ESD 90 black

_

> 390°C

1. Company	
Name/Address	Röchling Industrial SE & Co. KG Röchlingstr. 1 • 49733 Haren (Ems)/Germany (DE) • Tel. +49 5934 701-0 info@roechling-plastics.com • www.roechling.com/industrial/haren
2. Product details	
Product/Article	Technical semi-finished product or machined part
Abbreviated terms	PE-UHMW / PE 1000
Material Characterisation	Semi crystalline plastic
Main Components	 polyethylene possibly olefin-copolymerisate stabiliser additives
Components Subject to labe	lling none
Classification according to R	EACh Article
Notes	-
3. Product characteristics	
Form/State	• firm
Color	black
Odour	nearly odourless
Density	>0,94
Melting range	130 135



Print: 01/05/2025 • Release: 20/09/2023 • Version: 1.0 PIM-Version: 772 • PIM-ID: 591221 • PIM-Code: 772-16

Glass transition temperature

Thermal decomposition

Röchling

3. Product characteristics			
Flash point	≈ 340°C		
Ignition temperature	> 350°C		
Notes	-		

4. Danger warnings							
Special Risks For Mankind And Th Environment	none						
Notes							
5. Handling and Storage							
Handling	 Product can be worked with conventional machines and tools. Before machining the product should have room temperature and/or to be stored for min. 24h under normal climatic conditions. 						
Storage	 horizontally dry protected against frost protected against climatic influences 						
Safety measures	Protect against overheating.Carry protective mask and eye protector with dusty condition.						
Shelf Life							

6. Transport					
Transport	 Non dangerous goods according to the transport regulations. Secure against slipping. 				
Finished Product Packing	-				
Notes	By the processing under high temperatures gases can outcome, this gases can cause irritation the eyes and respiratory tract.				

7. Fire – fighting measures



Print: 01/05/2025 • Release: 20/09/2023 • Version: 1.0 PIM-Version: 772 • PIM-ID: 591221 • PIM-Code: 772-16



Suitable extinguishing agents	• water				
	• foam				
	• CO ₂				
	 dry powder extinguishing agents 				
Potential combustion products	• CO				
	• CO ₂				
Necessary protection equipment	Complete protection equipment for fire-brigade.				
Notes	Molten product has to be cooled with water. Fireresidues must be collected and disposed according to the local instructions.				

8. Removal	
Recyclability	Check possibility of recycling.
EC Waste Catalog	The product is classified in accordance with the European-Waste Catalogue (EWC) as "not dangerous".
Waste Removal	Has to be conveyed to a suitable dumping site or combustion plant in accordance with local regulations.
EC Waste Code	 12 01 05 plastics shavings and turnings 20 01 39 plastics
Notes	-

9. Marking and Guidelines						
Marking in accordance with Guideline	EEC	no labelling r	required			
Notes		-				

10. Information about REACh					
Information about REACh	According to EC directive 1907/2006/EC (REACh), Article 3, no.3 our products are clearly defined as articles, exempt from registration. The EU regulation about chemicals no. 1907/2006 (REACh), which came into force 01 st of June 2007, prescribes Material Safety Data Sheets only for dangerous substances and preparations. According to REACh we are manufacturing articles and, therefore, not required to issue safety sheets.				

11. Other Information



Print: 01/05/2025 • Release: 20/09/2023 • Version: 1.0 PIM-Version: 772 • PIM-ID: 591221 • PIM-Code: 772-16



Industrial

Other Information

The information in this document are based on our today's knowledge and represent no affirmation of characteristics.Existing laws and regulations are to be observed by the user of our product within his own responsibility.





Print: 01/05/2025 • Release: 20/09/2023 • Version: 1.0 PIM-Version: 772 • PIM-ID: 591221 • PIM-Code: 772-16