

# **Product Handling Information Sheet**

> 390°C

## Polystone<sup>®</sup> M ESD 90 black

1. Company	
Name/Address	Röchling Industrial SE & Co. KG Röchlingstr. 1 • 49733 Haren (Ems)/Germany (DE) • Tel. +49 5934 701-0 info@roechling-plastics.com • www.roechling.com/industrial/haren
2. Product details	
Product/Article	Technical semi-finished product or machined part
Abbreviated terms	PE-UHMW / PE 1000
Material Characterisation	Semi crystalline plastic
Main Components	<ul> <li>polyethylene</li> <li>possibly olefin-copolymerisate</li> <li>stabiliser</li> <li>additives</li> </ul>
Components Subject to labellin	ng none
Classification according to REA	ACh Article
Notes	-
3. Product characteristics	
Form/State	• firm
Color	black
Odour	nearly odourless
Density	>0,94
Melting range	130 135
Glass transition temperature	-



Thermal decomposition



Flash point	≈ 340°C	
Ignition temperature	> 350°C	
Notes	-	

4. Danger warnings						
Special Risks For Mankind And The Environment		none				
Notes		-				
5. Handling and Storage						
Handling		<ul> <li>Product can be worked with conventional machines and tools.</li> </ul>				
		<ul> <li>Before machining the product should have room temperature and/or to be stored for min. 24h under normal climatic conditions.</li> </ul>				

Handling	<ul> <li>Product can be worked with conventional machines and tools.</li> <li>Before machining the product should have room temperature and/or to be stored for min. 24h under normal climatic conditions.</li> </ul>
Storage	<ul> <li>horizontally</li> <li>dry</li> <li>protected against frost</li> <li>protected against climatic influences</li> </ul>
Safety measures	<ul><li>Protect against overheating.</li><li>Carry protective mask and eye protector with dusty condition.</li></ul>
Shelf Life	_
Notes	-

6. Transport				
Transport	<ul> <li>Non dangerous goods according to the transport regulations.</li> <li>Secure against slipping.</li> </ul>			
Finished Product Packing	-			
Notes	By the processing under high temperatures gases can outcome, this gases can cause irritation the eyes and respiratory tract.			

#### 7. Fire – fighting measures



### **Industrial**



Suitable extinguishing agents	• water
	• foam
	• CO <sub>2</sub>
	<ul> <li>dry powder extinguishing agents</li> </ul>
Potential combustion products	• CO
	• CO <sub>2</sub>
Necessary protection equipment	Complete protection equipment for fire-brigade.
Notes	Molten product has to be cooled with water. Fireresidues must be collected and disposed according to the local instructions.

8. Removal	
Recyclability	Check possibility of recycling.
EC Waste Catalog	The product is classified in accordance with the European-Waste Catalogue (EWC) as "not dangerous".
Waste Removal	Has to be conveyed to a suitable dumping site or combustion plant in accordance with local regulations.
EC Waste Code	<ul><li>12 01 05 plastics shavings and turnings</li><li>20 01 39 plastics</li></ul>
Notes	-

9. Marking and Guidelines					
Marking in accordance with Guideline	EEC	no labelling r	required		
Notes		-			

10. Information about REACh				
Information about REACh	According to EC directive 1907/2006/EC (REACh), Article 3, no.3 our products are clearly defined as articles, exempt from registration. The EU regulation about chemicals no. 1907/2006 (REACh), which came into force 01 st of June 2007, prescribes Material Safety Data Sheets only for dangerous substances and preparations. According to REACh we are manufacturing articles and, therefore, not required to issue safety sheets.			

#### 11. Other Information







Other Information

The information in this document are based on our today's knowledge and represent no affirmation of characteristics. Existing laws and regulations are to be observed by the user of our product within his own responsibility.



