

## **Product Handling Information Sheet**

## Polystone® M Slide + AST grey

1. Company				
Name/Address	Röchling Industrial SE & Co. KG Röchlingstr. 1 • 49733 Haren (Ems)/Germany (DE) • Tel. +49 5934 701-0 info@roechling-plastics.com • www.roechling.com/industrial/haren			
2. Product details				
Product/Article	Technical semi-finished product or machined part			
Abbreviated terms	PE-UHMW / PE 1000			
Material Characterisation	Semi crystalline plastic			
Main Components	<ul> <li>polyethylene</li> <li>possibly olefin-copolymerisate</li> <li>stabiliser</li> <li>additives</li> </ul>			
Components Subject to labellin	ng none			
Classification according to REA	ACh Article			
Notes	-			
3. Product characteristics				
Form/State	• firm			
Color	grey			
Odour	nearly odourless			
Density	>0,95			
Melting range	130 135			
Glass transition temperature	-			
Thermal decomposition	> 390°C			





3. Product characteristics	~740°C			
Flash point	≈ 340°C			
Ignition temperature	> 350°C			
Notes	<del>-</del>			
4. Danger warnings				
Special Risks For Mankind And Tl Environment	ne none			
Notes	-			
5. Handling and Storage				
Handling	Product can be worked with conventional machines and tools.			
	<ul> <li>Product can be worked with conventional machines and tools.</li> <li>Before machining the product should have room temperature and/or to be</li> </ul>			
	stored for min. 24h under normal climatic conditions.			
Storage	horizontally			
	• dry			
	protected against frost			
	protected against climatic influences			
Safety measures				
Shelf Life				
Notes	-			
6. Transport				
Transport	Non dangerous goods according to the transport regulations.			
•	Secure against slipping.			
Finished Product Packing	-			
Notes	-			
-				



7. Fire – fighting measures





Suitable extinguishing agents	• water
	• foam
	• CO <sub>2</sub>
	<ul> <li>dry powder extinguishing agents</li> </ul>
Potential combustion products	• CO
	• CO <sub>2</sub>
Necessary protection equipment	Complete protection equipment for fire-brigade.
Notes	Molten product has to be cooled with water. Fireresidues must be collected and disposed according to the local instructions.

8. Removal	
Recyclability	Check possibility of recycling.
EC Waste Catalog	The product is classified in accordance with the European-Waste Catalogue (EWC) as "not dangerous".
Waste Removal	Has to be conveyed to a suitable dumping site or combustion plant in accordance with local regulations.
EC Waste Code	<ul><li>12 01 05 plastics shavings and turnings</li><li>20 01 39 plastics</li></ul>
Notes	-

7. Marking and Galdennes				`	
Marking in accordance with Guideline	EEC	no labelling r	equired		
Notes		-			

10. Information about REACh		
ormation about REACh	Information about REACh Text	

11. Other Information	
Other Information	The information in this document are based on our today's knowledge and represent no affirmation of characteristics. Existing laws and regulations are to be observed by the user of our product within his own responsibility.

