

Product Handling Information Sheet

> 390°C

Polystone® MK FL + AST black pressed

| 1. Company | | | | | | |
|-------------------------------|-------|---|--|--|--|--|
| Name/Address | | Röchling Industrial SE & Co. KG Röchlingstr. 1 • 49733 Haren (Ems)/Germany (DE) • Tel. +49 5934 701-0 | | | | |
| | | info@roechling-plastics.com • www.roechling.com/industrial/haren | | | | |
| | | | | | | |
| 2. Product details | | | | | | |
| Product/Article | | Technical semi-finished product or machined part | | | | |
| Abbreviated terms | | PE-UHMW / PE 1000 | | | | |
| Material Characterisation | | Semi crystalline plastic | | | | |
| Main Components | | polyethylene possibly olefin-copolymerisate stabiliser additives | | | | |
| Components Subject to labe | lling | none | | | | |
| Classification according to R | EACh | Article | | | | |
| Notes | | - | | | | |
| 3. Product characteristics | | | | | | |
| Form/State | | • firm | | | | |
| Color | | black | | | | |
| Odour | | nearly odourless | | | | |
| Density | | >1,0 | | | | |
| Melting range | | 130 135 | | | | |
| Glass transition temperature | | - | | | | |



Thermal decomposition



| 3. Product characteristics | |
|---|--|
| Flash point | ≈ 340°C |
| Ignition temperature | > 350°C |
| Notes | - |
| | |
| 4. Danger warnings | |
| Special Risks For Mankind And Tl Environment | ne none |
| Notes | - |
| | |
| | |
| 5. Handling and Storage | |
| Handling | Product can be worked with conventional machines and tools. |
| ŭ | Before machining the product should have room temperature and/or to be |
| | stored for min. 24h under normal climatic conditions. |
| Storage | horizontally |
| | • dry |
| | protected against frost |
| | protected against climatic influences |
| Safety measures | |
| Shelf Life | |
| Notes | - |
| | |
| | |
| 6. Transport | |
| Transport | Non dangerous goods according to the transport regulations. |
| | Secure against slipping. |
| Finished Product Packing | - |
| | |



7. Fire – fighting measures

Industrial



| • water |
|--|
| • foam |
| • CO ₂ |
| dry powder extinguishing agents |
| • CO |
| • CO ₂ |
| Complete protection equipment for fire-brigade. |
| Molten product has to be cooled with water. Fireresidues must be collected and disposed according to the local instructions. |
| |

| 8. Removal | |
|------------------|---|
| Recyclability | Check possibility of recycling. |
| EC Waste Catalog | The product is classified in accordance with the European-Waste Catalogue (EWC) as "not dangerous". |
| Waste Removal | Has to be conveyed to a suitable dumping site or combustion plant in accordance with local regulations. |
| EC Waste Code | 12 01 05 plastics shavings and turnings20 01 39 plastics |
| Notes | - |

| 9. Marking and Guidelines | | | | | | |
|--------------------------------------|-----|----------------|----------|--|--|--|
| Marking in accordance with Guideline | EEC | no labelling ı | required | | | |
| Notes | | - | | | | |

| 10. Information about REACh | | | | | |
|-----------------------------|---|--|--|--|--|
| Information about REACh | According to EC directive 1907/2006/EC (REACh), Article 3, no.3 our products are clearly defined as articles, exempt from registration. The EU regulation about chemicals no. 1907/2006 (REACh), which came into force 01 st of June 2007, prescribes Material Safety Data Sheets only for dangerous substances and preparations. According to REACh we are manufacturing articles and, therefore, not required to issue safety sheets. | | | | |

11. Other Information







Other Information

The information in this document are based on our today's knowledge and represent no affirmation of characteristics. Existing laws and regulations are to be observed by the user of our product within his own responsibility.



