

## **Product Handling Information Sheet**

## Polystone® PVDF SK natural

1. Company		
Name/Address	Röchling Industrial SE & Co. KG Röchlingstr. 1 • 49733 Haren (Ems)/Germany (DE) • Tel. +49 5934 701-0 info@roechling-plastics.com • www.roechling.com/industrial/haren	
2. Product details		
Product/Article	Technical semi-finished product or machined part	
Abbreviated terms	PVDF	
Material Characterisation	Semi crystalline plastic with polyester fabrics	
Main Components	polyvinylidene fluoride	
Components Subject to labelli	none	
Classification according to RE	Article	
Notes		
3. Product characteristics		
Form/State	• firm	
Color	natural	
Odour	nearly odourless	
Density	>1,75	
Melting range	172 175	
Glass transition temperature	-	
Thermal decomposition	> 350°C	
Flash point	<u>-</u>	
Ignition temperature	<u> </u>	





3. Product characteristics		
Notes		
4. Danger warnings		
Special Risks For Mankind A Environment	The none	
Notes	<del>-</del>	
5. Handling and Storage		
Handling	<ul> <li>Product can be worked with conventional machines and tools.</li> <li>Before machining the product should have room temperature and/or stored for min. 24h under normal climatic conditions.</li> <li>When welding do not exceed the recommended air and tool temperat</li> <li>By disregarding the instructions the staff can falls in Fluor fever (fever like symptoms).</li> <li>At the first sign a doctor should be consulted.</li> <li>Plant parts should be grounded.</li> <li>Carry out processing in such a way that there is no thermal decompose.</li> </ul>	tures. with flu-
Storage	<ul> <li>horizontally</li> <li>dry</li> <li>protected against frost</li> <li>protected against climatic influences</li> </ul>	
Safety measures	• In case of inhalation of decomposition products: - Take to fresh air.	
Shelf Life	-	
Notes		
6. Transport		
Transport	<ul><li>Non dangerous goods according to the transport regulations.</li><li>Secure against slipping.</li></ul>	
Finished Product Packing	_	
Notes	Product protect against open flames.	





Suitable extinguishing agents		• water
		• foam
		• CO <sub>2</sub>
		<ul> <li>dry powder extinguishing agents</li> </ul>
Potential combustion products		hydrofluoric acid
		• CO
		low molecular fluorocarbon
Necessary protection equipment		Complete protection equipment for fire-brigade.
Notes		Molten product has to be cooled with water. Fireresidues must be collected and disposed according to the local instructions.
8. Removal		
Recyclability		Check possibility of recycling.
EC Waste Catalog		The product is classified in accordance with the European-Waste Catalogue (EWC) as "not dangerous".
Waste Removal		Has to be conveyed to a suitable dumping site or combustion plant in accordanc with local regulations.
EC Waste Code		<ul><li>12 01 05 plastics shavings and turnings</li><li>20 01 39 plastics</li></ul>
Notes		-
9. Marking and Guidelines		
Marking in accordance with Guideline	EEC	no labelling required
Notes		The material does not contain constituents that exhibit endocrine disrupting properties in quantities of 0.1% or more in accordance with REACH Article 57(f) of Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605.



10. Information about REACh





Information about REACh

According to EC directive 1907/2006/EC (REACh), Article 3, no.3 our products are clearly defined as articles, exempt from registration. The EU regulation about chemicals no. 1907/2006 (REACh), which came into force 01 st of June 2007, prescribes Material Safety Data Sheets only for dangerous substances and preparations. According to REACh we are manufacturing articles and, therefore, not required to issue safety sheets.

## 11. Other Information

Other Information

The information in this document are based on our today's knowledge and represent no affirmation of characteristics. Existing laws and regulations are to be observed by the user of our product within his own responsibility.



