

Polyamide with built-in fire protection

Sustamid® 6 FR - An economic solution for small up to medium quantities

- Extruded semi-finished products made of flame-retardant polyamide 6 (PA 6)
- Available as sheets, rods and tubes
- Enables the production of large-scale machined parts and components in small quantities

Properties

- Very high oxygen index of 40 % (LOI Limiting Oxygen Index)
- Flame resistant (V0 according to UL 94)
- Halogen free
- · Good dimensional stability and high strength and rigidity
- · Good slide and wear behaviour
- Low density (1.17 g/cm³)

Markets


Sustamid® 6 FR is the ideal material for applications in which very high demands are placed on flammability, mechanical properties and weight.

- Rail vehicle construction
- Aviation industry
- · Ship building
- Mining

- Oil & Gas
- Healthcare
- Vehicle construction



Sustamid® 6 FR: Enables the production of machined parts and components in small quantities – for example brackets, bushes, enclosures or manifolds and housings



Cable clamp made of Sustamid® 6 FR: the flameresistant material allows extruded PA 6 to be used in areas with high demands on flammability

Approvals

| Standard | Country | Fulfilled Testing R22, R23, R24, R25, R26 | |
|--------------------------------|-----------------------|---|--|
| EN 45545 | Europe | | |
| BS 6859 | UK | Table 7 / Table 8 | |
| DIN 5510 | DE | S4 / SR2 / ST2 | |
| BSS 7239 | USA/SEA | Toxic gas generation Surface flammability Smoke generation V0 | |
| NFPA130 – ASTM E162 | USA/SEA | | |
| NFPA130 – ASTM E662 | USA/SEA | | |
| UL 94 | Worldwide | | |
| FAR 25.853 | Worldwide (Airbus) | Finished | |
| Japan Railway Ignition Test | JP | (3) flame retardant | |

Stock and delivery programme

| Sheets | Color | Format (mm) | Thickness (mm) |
|--------|---------|---------------|---|
| | Natural | 620 x 3,000 | 6/8/10/12/16/20/25/30/40/ 45/50/60/90 |
| | Black | 620 x 3,000 | 15/20/25/30/35/40/45/50/60 |
| New | Black | 2,000 x 1,000 | 3/5/12 |
| Rods | Color | Length (mm) | Diameter (mm) |
| | Natural | 3,000 | 12/16/20/30/40/50/60/70/100 (80 on request) |
| Black | Black | 3,000 | 30/70/100 |
| Tubes | Color | Length (mm) | Outer & inner Diameter (mm) |
| New | Natural | 3,000 | 10/5; 12/7; 13/8; 14/9; 15/10; 16/11; 18/13; 20/15; 25/20; 30/25; 32/27; 36/31 (on request) |

Numbers in bold = ex stock, short delivery time! Other delivery forms and sizes are possible on request

Röchling Industrial. Empowering Industry. www.roechling-industrial.com

