

Technical Data Sheet

Fibracon[®] PTFE + 20% Polyimide

PTFE

Typical characteristics

- Good dimensional stability
- Good wear resistance

Typical industries

- Chemical Processing Industry
- Vehicle Construction
- Electronics
- Oil and Gas
- Mechanical Engineering Industry
- Healthcare
- Food Industry
- Wind Energy

| | Test method | Unit | Guideline value |
|------------------------------|-------------|---------------------|-----------------|
| General properties | | | |
| Density | ASTM 4894 | g / cm ³ | 1.86 |
| Mechanical properties | | | |
| Hardness | Needle | Shore D | 61 |
| Tensile Strength (23°C) | ASTM 4894 | MPa | 14 |
| Elongation at Break | ASTM 4894 | % | 190 |
| Thermal properties | | | |
| Service Temperature | | °C | -200 to +260 |

This data provides typical values on a small selection of properties of the material and should only be used as a guide to the generic material performance.

ri-inquiry@roechling.com • www.roechling.com/industrial/materials

Print: 28/07/2025 • Release: 20/09/2023

PIM-Version: 35 • PIM-ID: 709612 • PIM-Code: 35-40-153.143-7.7.8.5.5.9.5.10-1

Company-IDs: 21220

Page 1 / 1 (Dates in DD/MM/YYYY)

