

## Technical Data Sheet

# Polystone® Extreme Wear dump bed liner

PE-UHMW / PE 1000

### Typical characteristics

- Good sliding properties
- High impact resistance
- High abrasion resistance

### Typical industries

- Heavy-Duty Truck Products

	Test method	Unit	Guideline value
<b>General properties</b>			
Density	ASTM D792	g / cm <sup>3</sup>	0.93
<b>Mechanical properties</b>			
Tensile Strength at Yield	ASTM D638	psi	2800
Elongation at Break	ASTM D638	%	400
Flexural Modulus	ASTM D790	psi	90000
Rockwell Hardness	ASTM D785	R	67
<b>Thermal properties</b>			
Continuous Use		°F	180
<b>Electrical properties</b>			
Volume Resistivity	ASTM D257	Ωcm	>10 <sup>16</sup>
Surface resistivity	ASTM D257	Ω/cm	>10 <sup>16</sup>

The data stated above are average values ascertained by statistical tests on a regular basis. The data above are provided purely for information and shall not be regarded as binding unless expressly agreed in a contract of sale.

[ri-inquiry@roechling.com](mailto:ri-inquiry@roechling.com) • [www.roechling.com/industrial/materials](http://www.roechling.com/industrial/materials)

Print: 05/12/2025 • Release: 20/08/2025 • Version: 2.0  
PIM-Version: 45 • PIM-ID: 717988 • PIM-Code: 45-21-223.18.63-6-2  
Company-IDs: 23070

Page 1 / 1 (Dates in DD/MM/YYYY)

